

# THE RESILIENT

WITH STRONG HYDRAULIC DRIVE  
AND HARDEST  
WORKLOADS  
GRIDS



UP TO 800  
SLICES/MINUTE

FOR THE INDUSTRY

**MHS**  
SCHNEIDETECHNIK GMBH



## EASY HANDLING

Manually via knobs and buttons or via touch display, including storable programs and infinitely variable pre-compressing.



## SMART CUTTING SYSTEM

Accurate cut by long stroke of cutting grid and pulling cut of the cutting blade.



## CUTS ...

Meat, fat, bacon, ham, onions, peppers, fish, cheese, sausages, eggs and lots more.



## SMART HYGIENE

The construction reduces the dirt to a minimum and simplifies cleaning.





TOOLLESS  
HANDLING



INTUITIVE  
OPERATION



QUIET  
SLICING



EASY TO  
CLEAN



ENERGY  
SAVING

# MHS

SCHNEIDETECHNIK GMBH

## MHS 2900

The multi-purpose dicer MHS 2900 is ideal for industry, with a throughput of up to 2900 kg per hour. The machine is a convincing performer thanks to its hydraulic system and highly resilient grid drives.

### PRODUCTIVITY

- Up to 2900 kg/h
- Up to 800 slices/minute
- Long lifetime thanks to soft start and sturdy cutting grid
- Automatic operation using a hopper

### SLICING RESULTS

- Choice of clogged or continuous feeding
- Adjustable horizontal compression
- Reinforced grid with 4x suspension for highest workload



### VERSATILITY

- Uses slicing discs for cutting slices and strips
- Optional feeding via infeed belt
- Hopper for bulk solids for integration into automatised production systems
- Comprehensive range of accessories (see page 16)

### HANDLING

- No pre-slicing required thanks to the automatically closing cross blade
- Dual chamber system with simultaneous machine loading and slicing
- User friendly, easy adjustment of all slicing parameters
- Outfeed belt for discharging product in 200 litre trolleys or containers of your choice

## NUMEROUS POSSIBLE MACHINE EQUIPMENT E.G.



• OUTFEED BELT



• PEDESTAL FOR DIRECT OUTLET INTO 200 LITER TROLLEY



• FORWARD FEED BELT AND HOPPER

<b>Max. input length:</b>	620 mm
<b>Cross section (WxH):</b>	
MHS 2900-120 / -220	120 x 120 mm / 120 x 120 mm
Open	120 x 120 mm / 220 x 120 mm
<b>Throughput (kg/h):</b>	
MHS 2900-120 / -220	2900 / 3200
<b>Cutting length (mm):</b>	0 – 50 mm
<b>Connection:</b>	
MHS -120 / -220	3Ph + PE 400V 50 Hz 6.5 kW / 9.5 kW

FOR MORE MACHINES VISIT  
[WWW.MHS-SCHNEIDETECHNIK.DE](http://WWW.MHS-SCHNEIDETECHNIK.DE)

FURTHER TECHNICAL DATA AND  
OVERVIEW OF MODELS ON PAGE 18